

Electrical Parameters	Input Voltage	AC85-265V	Power Factor	> 0.95
	LED Type	SAMSUNG	LED Initial Flux	160-170LM/W
			Lamp Initial Flux	120LM/W ± 5%
		CREE	LED Initial Flux	160-170LM/W
			Lamp Initial Flux	95LM/W ± 5%
	Working Life	50000 hours	CCT	2700-6500K
	Power Efficiency	> 90%	Beam Angel	15/35/45/60/110°
	IP Grade	IP65	Working Temperature	-40°C +60°C
Model	LED Power	LED Quantity	Lamp Size(mm)	Net Weight(kg)
CO-T300-50W	50W	24*1PCS (CREE) 72*1PCS(SAMSUNG)	238*102*178	2.1+5%
CO-T300-100W	100W	48*1PCS (CREE) 144*1PCS(SAMSUNG)	238*219*227	3.2 +5%
CO-T300-150W	150W	72*1PCS (CREE) 216*1PCS(SAMSUNG)	238*340*227	4.1 +5%
CO-T300-200W	200W	96*1PCS (CREE) 288*1PCS(SAMSUNG)	425*219*227	5.5+5%
CO-T300-300W	300W	144*1PCS (CREE) 432*1PCS(SAMSUNG)	425*340*227	8.4+5%